



PRODUCT FEATURES

AVAILABLE IN 30, 45, 60, 75, 90, 105, & 120 THOUSAND BTU

STANDARD FEATURES

- 81% Thermal Efficiency
- Redundant Single Stage Gas Valve
- Residential Certification
- 20GA Aluminized Heat Exchanger
- 120/24V Control Transformer
- 115/1/60 Fan Motor with Internal Overload Protection
- Power Vented
- Direct Spark Ignition
- 20GA Baked Enamel Cabinet
- 10 Year Heat Exchanger Warranty
- OSHA Fan Guard
- Right Hand Control Access
 - Field Convertible to Left Hand
- High Limit Switch
- Air Pressure Switch
- Natural or Propane Gas
- Gas Conversion Kit Included
- Field Convertible to Separated Combustion
- Easy Access Control Panel
- 321 Stainless Steel Burner Box



OPTIONAL EQUIPMENT

- 409 Stainless Steel Heat Exchanger
 - Two Stage Gas Control (Sizes 60-120 Only)
 - Supply Voltage (Field Mounted Transformers):
 - 208/1/60
 - 230/1/60
 - 208/3/60
 - 230/3/60
 - 460/3/60
 - 575/3/60
 - Totally Enclosed Motors (Sizes 60-120 Only)
 - 409 Stainless Steel Flue Collector
 - Pressure Regulator (1/2 – 2 psi)
 - Single & Two Stage Mercury Free Thermostats
 - Line Volt Thermostat
 - Locking Thermostat Cover
 - 24V SPST Relay
 - Vent Caps
 - Concentric Vent Kits
- (For All Separated Combustion Installations)



Model GG045



Model GG045



Model GG120



Model GG120



260 North Elm St., Westfield, MA 01085
(413) 564-5540 Fax: (413) 562-5311
www.sterlinghvac.com